



3.7 Meter Dual Reflector Pedestal Mount

The ASC Signal 3.7 meter dual reflector pedestal mount earth station antenna provides extremely accurate surface contour, high gain and superior efficiency.

The versatile pedestal mount allows for fixed or motorized applications and features 180 degree azimuth coverage in three continuous overlapping ranges.

The aluminum hub and hot-dipped galvanized steel mount maintains pointing accuracy and ensures durability and reliability.

- High gain and excellent pattern characteristics
- Gregorian Optics
- Self-aligning main reflector
- 180 mph high wind option (manual antennas)
- 3 year warranty on all structural components
- Eutelsat Type Approval, 2-Port Ku-band EA-A002
- Asiasat Approval, Type 2
- Apstar Approval
- INTELSAT® Approval, E-2 at Ku-band: IA12A00, 2-Port; IA12B00, 4-Port
- U.S. FCC Regulation 25.209 at Ku-band Approval
- Russian Homologation Certificate OC/1-AO-136



SPECIFICATIONS

3.7 Meter Dual Reflector Pedestal Mount

Electrical Performance

	Ku-band 2-Port Linear Pol Feed		Ku-band 4-Port Linear Pol Feed		K-band 2-Port Linear Pol Feed		K-band 4-Port Linear Pol Feed		C-band 2-Port Circular Pol Feed	
	Receive	Transmit	Receive	Transmit	Receive	Transmit	Receive	Transmit	Receive	Transmit
Frequency (GHz)	10.700-12.750	13.750-14.800	10.700-12.750	13.750-14.800	10.700-12.750	17.300-18.400	10.700-12.750	17.300-18.400	3.625-4.200	5.850-6.425
Insertion Loss dB	0.15	0.20	0.20	0.30	N/A	N/A	0.20	0.30	0.15	0.20
Gain @ Feed Output Flange (dBi ± 0.2 dB)										
3.625 GHz	N/A		N/A		N/A		N/A			40.50
5.850 GHz	N/A		N/A		N/A		N/A			45.30
10.700 GHz	50.60		50.00		50.50		N/A			N/A
12.750 GHz	52.10		51.70		51.90		N/A			N/A
13.750 GHz	52.50		52.20		N/A		N/A			N/A
14.800 GHz	53.30		53.00		N/A		N/A			N/A
17.300 GHz	N/A		N/A		N/A		54.20			N/A
18.400 GHz	N/A		N/A		N/A		54.60			N/A
Antenna Noise Temperature										
10° Elevation		52 K		52 K		52 K		73 K		42 K
30° Elevation		39 K		39 K		39 K		57 K		37 K
50° Elevation		37 K		37 K		37 K		54 K		35 K
Port-to-Port Isolation										
Rx to Rx		40 dB		40 dB		40 dB		40 dB		85 dB
Tx to Rx		40 dB		85 dB		40 dB		80 dB		40 dB
Waveguide Interface Flange										
	Brass WR75	Brass WR75	Brass WR75G	Brass WR75G	Brass WR75	Brass WR75	WR75	WR62	CPR-137	CPR-229
Tx Power Capacity										
	2000 W		2000 W		1000 W		1000 W/Per Port		500 W	
Maximum Pressurization										
	0.50 psi		0.50 psi		0.50 psi		0.50 psi		0.50 psi	

Mechanical Performance

Optics Type	Dual Reflector, Gregorian
Reflector Material	Precision Formed Aluminum
Reflector Segments	2
Hub/Enclosure Dimensions Diameter	1.22 m (48.00 in)
 Depth	0.61 m (24.00 in)
Mount Type	Pedestal
Antenna Pointing Range, Course		
 Elevation	0° - 90°
 Azimuth	180° Coarse, 120° Continuous

Environmental Performance

Operational Temperature	-45.5°C to 52°C (-50°F to 125°F)
Wind Loading Survival	105 km/h (65 mph) (with or without Motor Drives)
 Operational	72 km/h (45 mph) with Gusts to 105 km/h (65 mph) (with or without Motor Drives)
Rain	102 mm (4 in per hour)
Solar Radiation	360 BTU/hr/ft ² (1135 W/m ²)
Relative Humidity	100%
Shock and Vibration	As Encountered by Commercial Air, Rail and Truck
Atmospheric Conditions	As Encountered by Moderately Corrosive Coastal and Industrial Areas

