

## Isolated Ground SMA Female to SMA Female Bulkhead Adapter with Plastic Isolator



## **TECHNICAL DATA SHEET**

**PE9067** 

## Isolated Ground SMA Female to SMA Female Bulkhead Adapter with Plastic Isolator

Configuration

Connector 1 SMA Female Connector Specification 1 MIL-STD-348 Connector 2 **SMA Female** MIL-STD-348 Connector Specification 2 Adapter Design Standard Body Style Straight Bulkhead Mount Method Isolated Ground / Hermetic Isolated Ground

**Electrical Specifications** 

Impedance, Ohms 5

**Mechanical Specifications** 

Size

 Length, in [mm]
 0.875 [22.23]

 Width/Dia., in [mm]
 0.44 [11.18]

 Dielectric Type
 PTFE

Connector 1

Type SMA Female

Inner Conductor Material and Plating

Beryllium Copper, Gold
Body Material and Plating

Brass, Nickel

Connector 2

Type SMA Female

Inner Conductor Material and Plating Beryllium Copper, Gold

Body Material and Plating Brass, Nickel

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant Yes

Plotted and Other Data

Notes: Values at 25 °C, sea level
Plastic Isolator included

URL: http://www.pasternack.com/sma-female-sma-female-straight-adapter-pe9067-p.aspx

Isolated Ground SMA Female to SMA Female Bulkhead Adapter with Plastic Isolator from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



**PE9067 CAD Drawing**Isolated Ground SMA Female to SMA Female Bulkhead Adapter with Plastic Isolator

