

Low power terminations, up to 2 Watts

QN, 50 Ω

Frequency (GHz)	VSWR max.	Power rating (W)	Interface characteristics	HUBER+SUHNER type	Item no.
6	1.15	1	male	65_QN-50-0-2	84015257



SK, 50 Ω

Frequency (GHz)	VSWR max.	Power rating (W)	Interface characteristics	HUBER+SUHNER type	Item no.
40	1.22	1	male	6500.42.0001	84000377



SMA, 50 Ω

Frequency (GHz)	VSWR max.	Power rating (W)	Interface characteristics	HUBER+SUHNER type	Item no.
6	1.15	1	female	65_SMA-50-0-35	23015765
	1.25		male	65_SMA-50-0-20	23035247
	1.15		male ¹⁾	65_SMA-50-0-25	84028132
18	1.1	0.75	male	6500.19.A	22645868
	1.15	0.75	female	6500.19.B	22645869
	1.25	1	female	65_SMA-50-0-31	22550158
			male	65_SMA-50-0-1	22640162



¹⁾ Notes: Products with chain.

SMB, 50 Ω

Frequency (GHz)	VSWR max.	Power rating (W)	Interface characteristics	HUBER+SUHNER type	Item no.
4	1.4	0.5	male	65_SMB-50-0-1	22550111
			female	65_SMB-50-0-31	22640230



SMC, 50 Ω

Frequency (GHz)	VSWR max.	Power rating (W)	Interface characteristics	HUBER+SUHNER type	Item no.
4	1.2	0.5	female	65_SMC-50-0-31	22550114
6	1.22	1	male	65_SMC-50-0-2	84011016



SMPX-U, 50 Ω

Frequency (GHz)	VSWR max.	Power rating (W)	Interface characteristics	HUBER+SUHNER type	Item no.
18	1.2	1	male ¹⁾	65_SMPX-U50-0-1	84066642
			female ¹⁾	65_SMPX-U50-0-2	84066643

¹⁾ Notes: Mates with SMP / GPO interfaces.

