



Features

- VSAT or Broadcast Configuration
- Integrated Auto Locate Controller with Manual Override
- Auto Locate and Peak Features along with Handheld Control Unit
- Carbon Fiber Reflector
- Handcranks Included
- Low Profile and Space-Optimizing Stowed Configuration
- Designed for Boom Mounted Single Thread Integration Packages up to 35 lbs
- Affordable SNG Applications
- Intelsat / FCC Compliant
- C Band and X Band Capable

Overview

The 1.5 Meter Vehicle-Mount VSAT Antenna from Advantech Wireless is designed to offer the end user affordable performance for VSAT or SNG applications in a compact design.

This antenna features an integrated auto-locate controller with manual override, carbon fiber composite reflector, handcranks, and an optional VSAT or low cross pol feed. The integrated control system includes a programmable digital video receiver capable of storing up to 10 satellite signposts that can be used to positively identify the satellite. Up to 35 lbs of payload can be mounted on the feedboom for multiple integration packages and options. High gain performance along with the precision surface and payload offer an optimum dB per dollar performance.

The antenna is designed to meet required Ku Band performance specifications for commercial applications.

PRODUCT FEATURES & SPECIFICATIONS

Technical Specifications

Electrical Specifications		2 Port Cross Pol Ku Band Linear / VSAT Feed		2 Port Cross Pol Ku Band Linear / Low Cross Pol Feed	
	Rx	Tx	Rx	Tx	
Frequency (GHz)	10.70 - 12.75	13.75 - 14.5	10.7 - 12.75	13.75 - 14.5	
Gain (Midband, dBi)	43.4	45.0	43.4	45.0	
Noise Temperature (°K)					
	10 deg El	70		65	
	20 deg El	60		58	
Axial Ratio					
Cross Pol					
	On Axis	-30 dB	-30 dB	-35 dB	-35 dB
	in 1 dB BW	-25 dB	-25 dB	-27 dB	-27 dB
Sidelobe Compliances		Meets ITU 580 FCC		Meets ITU 580 FCC	
VSWR	1.45:1	1.30:1	1.35:1	1.30:1	
Isolation					
Tx/Rx	-110 dB	0 dBm input	-85 dB	0 dBm input	
Rx/Tx	0 dBm input	-35 dB	0 dBm input	-35 dB	

Mechanical / Environmental Specifications

Reflector	1.5 meters (58.75 in) Carbon Fiber Reinforced Polymer
Reflector Configuration	Parabolic Single Offset, 0.78 F/D (16.9 deg offset)
Antenna Travel	
Azimuth	± 200° continuous
Elevation	0 - 90° of reflector bore sight
Polarization	± 90°
Antenna Drive Rate	
Azimuth	5.0°/sec
Elevation	2.5°/sec
Polarization	3.0°/sec
Temperature	
Operational	-17 to 50°C (0 - 122°F)
Survival	-30 to 70°C (-40 - 158°F)
Winds ¹	
Operational	40 mph (64 kph)
Survival	65 mph (104 kph) deployed any position 90 mph (144 kph) stowed
Antenna Stow Height	18 in (457 mm)
Weight	185 lb (84 kg) - with Ku Feed and controller
Integration ²	
Feedboom Mounted ³	35 lbs
Rain	
Operational	4 in/h (10 cm/h)
Survival	6 in/h (15 cm/h)
Relative Humidity	0 - 100%
Solar Radiation	360 btu/h/ft ² (1000 Kcal/h/m ²)
Corrosive Atmosphere	As encountered in coastal and/or industrial areas

¹ Dependent on vehicle capabilities

² Dependent on mounting position relative to elevation axis

³ Std weight shown, consult factory for special requirements

NORTH AMERICA USA

Tel: +1 703 659 9796
Fax: +1 703 635 2212
info.usa@advantechwireless.com

CANADA

Tel: +1 514 420 0045
Fax: +1 514 420 0073
info.canada@advantechwireless.com

EUROPE UNITED KINGDOM

Tel: +44 1480 357 600
Fax: +44 1480 357 601
info.uk@advantechwireless.com

RUSSIA & CIS

Tel: +7 495 971 59 18
info.russia@advantechwireless.com

INDIA

Tel: +91 33 2415 5922
info.india@advantechwireless.com

SOUTH AMERICA

Tel: +1 678 889-1831
Fax: +1 678 889-1756
info.latam@advantechwireless.com

BRAZIL

Tel: +55 11 3054 5701
Fax: +55 11 3054 5701
info.brazil@advantechwireless.com

An ISO 9001 : 2008 Company



Ref.: PB-VM-VSAT-1.5M-13150